



# NEW FROM SOLAX Triple Power 3.0



## Triple Power 3.0 Battery

### Features

- Systematic design, in-depth optimization and seamless connection with Solax Hybrid inverter
- Safest type of LiFePO<sub>4</sub> battery, an adoption of high-performance processors, international brand devices, better stability
- Unique battery heating technology, which is capable to work at low temperature
- Long life cycle, more than 6000 times
- Safety Cert. TUV, CE, UL, UN38.3 and so on
- Remote fault diagnosis, upgrade and maintenance
- Auto power replenishment technology is adopted to prevent battery over-discharge
- Multiple communication interfaces :RS485, CAN
- Modular stacking design, easy installation, supporting floor and wall mounting
- IP65, supporting indoor and outdoor installation

For more information, please contact us

www.solaxpower.com  
AU: +61 1300 476529  
DE: +49 6142 4091664

Global: +86 571-56260008  
UK: +44 2476 586998  
NL: +31 (0) 852 737932

info@solaxpower.com  
service@solaxpower.com



# Triple Power 3.0



	T-BAT H 3.0	T-BAT H 6.0*	T-BAT H 9.0*	T-BAT H 12.0*
Nominal voltage [V]	102.4	204.8	307.2	409.6
Operating voltage range [V]	90~116	180~232	270~348	360~464
Total energy [kWh]	3.1	6.1	9.2	12.3
Usable energy [kWh]	2.8	5.5	8.3	11.0
Rated capacity [Ah]			30	
Nominal power [kW]	2.55	5.1	7.65	10.2
Max. power [kW]	3.1	6.1	10.2	12.3
Recommend charge/discharge current [A]			25	
Max. charge/discharge current [A]			30	
Battery roundtrip efficiency			95%	
Cycle life [90% DOD]			6000 Cycles	
Expected life time / Warranty [year]			10	
Available charge/discharge temperature range [°C]			-30 to 50	
Storage temperature [°C]			-20 to 50 (3 months)	0 to 40 (1 year)
Humidity [%]			0~100	
Altitude [m]			Below 3000	
Degree of protection			IP65	
Battery to Inverter			RS485/CAN2.0	
Battery to battery/BMS			CAN2.0	
Master control capacity indicator			4LED (25%, 50%, 75%, 100%)	
Master control LED indicator (Working mode)			1 LED	
System switch (on/off)			Button*1+Breaker*1	
Certificate			CE/IEC62619/UN38.3/IEC62040/UKCA	
Hazardous materials classification			Class 9	
Dimensions(WxHxD) [mm]			MC0600: 482.5*173.5*153 HV10230: 482.5*471.5*153	
Net weight [kg]	MC0600: 7.5kg +HV10230: 34.5kg	MC0600: 7.5kg +2*HV10230: 69kg	MC0600: 7.5kg +3*HV10230: 103.5kg	MC0600: 7.5kg +4*HV10230: 138kg

\* MC0600:Master Box (one MC0600 can be connected 1~4 HV10230)

\* HV10230:Slave Battery Pack